


# Technical Information

Specification	<i>Renoir</i>	<i>VAN GOGH</i>	<i>Michelangelo</i>	<i>DA VINCI</i>	<i>art select</i>	<i>Knight-Tile</i>
<b>Thickness</b>	2.5mm	3mm	2.5mm	3mm [2.5mm at bevel]	3mm [2.5mm at bevel]	2mm
<b>Wear layer</b>	0.55mm	0.55mm	0.55mm	0.7mm	0.7mm	0.3mm
<b>Bevelled edge</b>	No	No	No	Yes	Yes	No
<b>Standards</b>	BS EN 649 ASTM F-1700					
<b>Reaction to fire</b>	EN 13501-1 ISO 9239-1 ISO 11925-2 ASTM E-648-04 ASTM E-662-03					
<b>Slip resistance</b>	BS 7976 EN 13893 ASTM C-1028 AS/NZS 4586 DIN 51130	BS 7976 EN 13893 ASTM C-1028 AS/NZS 4586 DIN 51130	BS 7976 EN 13893 ASTM C-1028 AS/NZS 4586 DIN 51130	BS 7976 EN 13893 ASTM C-1028 AS/NZS 4586 DIN 51130	BS 7976 EN 13893 ASTM C-1028 AS/NZS 4586 DIN 51130	BS 7976 EN 13893 ASTM C-1028 AS/NZS 4586 DIN 51130
<b>Staining resistance</b>	BS EN 423 ASTM F-925					
<b>Light fastness</b>	ISO105-B02 ASTM F-1515					
<b>Abrasion resistance</b>	BS EN 660-2					
<b>Dimensional stability</b>	BS EN 434 ASTM F-2199					
<b>Acoustic impact noise reduction</b>	BS EN ISO 140-8 BS EN ISO 717-2					
<b>Electrical behaviour body voltage</b>	BS EN 1815					
<b>Indentation – residual</b>	BS EN 433 ASTM F-1914					
<b>Castor chair continuous use</b>	EN 425					
<b>Thermal conductivity</b>	ISO 8302 0.0120m <sup>2</sup> /K/W	ISO 8302 0.0147m <sup>2</sup> /K/W	ISO 8302 0.0120m <sup>2</sup> /K/W	ISO 8302 0.0147m <sup>2</sup> /K/W	ISO 8302 0.0147m <sup>2</sup> /K/W	ISO 8302 0.0100m <sup>2</sup> /K/W
	Suitable for underfloor heating					
<b>Adhesive</b>	Acrylic HT [High Temperature] PS [Pressure Sensitive] Epoxy					
<b>Recycling</b>	Suitable					
<b>Wear classification</b>	EN 685:33 Commercial heavy	EN 685:33 Commercial heavy	EN 685:32 Commercial general	EN 685:34 Commercial very heavy	EN 685:34 Commercial very heavy	EN 685:23 Domestic heavy
	EN 685:42 Light industrial general	EN 685:42 Light industrial general	EN 685:41 Light industrial moderate	EN 685:43 Light industrial heavy	EN 685:43 Light industrial heavy	EN 685:31 Commercial moderate
<b>Box quantity</b>	3.34m <sup>2</sup> 3.30m <sup>2</sup> [16" Tiles]	3.25m <sup>2</sup> [Woodplanks]	3.34m <sup>2</sup> 3.30m <sup>2</sup> [16" Tiles]	3.34m <sup>2</sup> 3.30m <sup>2</sup> [16" Tiles]	2.046m <sup>2</sup> [Tiles] 3.25m <sup>2</sup> [Woodplanks] 2.12m <sup>2</sup> [Tudor Brick]	3.34m <sup>2</sup>



For full details of our Product Warranty/Guarantee terms please contact your supplier.

## Karndean UK

Crab Apple Way, Vale Park,  
Evesham, Worcestershire WR11 1GP  
Technical: 01386 820102  
Trade: 01386 820200  
Consumer: 01386 820100  
Accounts: 01386 820101  
Fax: 01386 761249  
technical@karndean.co.uk

## Karndean USA

1100 Pontiac Court,  
Bushy Run Corporate Park,  
Export, PA 15632  
Toll free phone: 888.266.4343  
Toll free fax: 800.887.7043  
info@karndean.com

## Karndean New Zealand

Unit A, 73 Greenmount Drive  
East Tamaki, Auckland  
P.O Box 58264  
Tel: 64 9 273 5430  
Fax: 64 9 273 5435  
info@karndean.co.nz

## Karndean Australia

835 Stud Road,  
Knoxfield,  
Victoria 3180  
Tel: 1800 33 11 70  
Fax: (03) 9763 1625  
enquiries@karndean.com.au

